

SIPOS 5 compatible relay card with 5 outputs „C54“

1 Use

This supplement applies to SEVEN actuators with "SIPOS 5 compatible relay card".

With this order option, the SEVEN is connection-compatible with the predecessor SIPOS 5 with relay card.



Please observe the corresponding operating instructions for "Electric actuators ECOTRON / PROFITRON / HiMod" and for fieldbus control "PROFIBUS-DP / Modbus RTU"!

2 Technical data

2.1 Relay outputs

Relay outputs are galvanically separated.

	DC for resistive load		AC
	max. switching capacity	150 W	
max. switching voltage	30 V	125 V	250 V
max. switching current	5 A	0,2 A	5 A

Actuators with „SIPOS 5 compatible relay card“ have 5 output signals (1x NO and 1x NC).

2.2 Variants

The option C54 „SIPOS 5 compatible relay card“ is available for SEVEN series actuators

- ECOTRON,
- PROFITRON and
- HiMod.

The option C54 „SIPOS 5 compatible relay card“ is not available

- in combination with fieldbus (order no. digit 14 not equal „B“),
- with additional analog card (order option C67/C68),
- with special binary input voltages (order option C60 to C63) or
- with wire break detection (order option C66).

3 Wiring diagrams

ECOTRON with SIPOS 5 compatible relay card „C54“	Y070.533
PROFITRON with SIPOS 5 compatible relay card „C54“	Y070.534
HiMod with SIPOS 5 compatible relay card „C54“	Y070.535